



COMPACT EXCAVATORS E17, E17z, E19, E20z

0-1 t | 1-2 t | 2-3 t | 3-4 t | 4-6 t | 6-10 t





INTRODUCTION

A PRODUCTIVITY MASTER





INDUSTRY-LEADING VISIBILITY Work safely day and night with a clear field of view, maximum visibility from inside the cab, and powerful LED lights.



• FIRST-CLASS COMFORT Feel right at home in a roomy cab fully designed around your needs. The temperature and fan speed control keep you comfortable throughout the working day.



• TRAVEL-FRIENDLY Enjoy hassle-free transportation with a 2.5-tonne trailer. The automatic slew brake and upper structure tiedowns give you extra peace of mind when you need it.



• COMPACT BY DESIGN Maneuver in tight spaces where other machines cannot. The retracted tracks and narrow frame are ideal for construction, renovation, utilities and landscaping.





POWER WHERE YOU NEED IT

RIGHT TOOL FOR THE JOB

In backyards, urban areas and other tight job sites, a big machine means big challenges. Bobcat machines allow operators to work in constrained environments, in extreme proximity to walls and other challenging situations.

PEACE OF MIND

Trust the machine in all situations. The Zero House Swing (ZHS) functionality provides 320° stability and flexibility of movement when working close to obstacles. Minimize the risk of potential damage while maximizing productivity.

PERFORMANCE


EFFICIENT POWER

Bobcat's unique E17 and E17z / E19 / E20z hydraulic systems make the best possible use of the engine's power. Fast cycle times, combined with smooth control of class-leading breakout forces, provide maximum productivity. Boom and dipper stick cylinder cushioning - unique in their class enhance overall smoothness.

▶ LIFT MORE, LIFT HIGHER

The superior dumping height makes loading trucks easy, while the reach at ground level means you don't need to reposition as often when digging. With enhanced stability and lifting capacity, combined with best-in-class proportional auxiliary flow, the Bobcat excavators offer you the highest versatility in operating a wide range of attachments.






Conventional tail swing



Zero House Swing (ZHS)



• PRECISION MEETS PRACTICALITY Step into the cab and immediately get to grips with the intuitive controls – ideal for both experienced and novice operators. Joysticks with all key functions in the right place; smooth travel pedals; and personalized controls for pinpoint accuracy.





BUILT TOUGH

TOUGH MATERIALS

Using highly durable materials makes the Bobcat excavators hard-wearing and robust.

- Rear tailgates protected by casted counterweights
- Oversized cylinders for long life
- New paint and surface treatment process
- Reinforced expandable undercarriage to enhance rigidity
- Cylinder covers for heavy applications

TESTED DESIGN

The design features are tested under extreme conditions and ensure extra durability and peace of mind while working.

- Metal covers can be opened or bolted on
- 2-piece blade cylinder hoses
- Wrenchless hydraulic hose technology helps prevent leakage
- Proven boom and dipper stick design
- Top-mounted boom cylinder

3

MACHINE IQ

BOBCAT® Machine IQ Wireless Communications enhances the support for your Bobcat machine.

- Durable built-in monitoring electronics
- Data is available to our machine monitoring specialist
 Maintenance is optimized
- for your business
- Data-driven services maximize uptime



Easy access to all vital components

▶ STANDARD WARRANTY Bobcat Company develops every machine to the highest standards of quality and durability. That's why our standard warranty provides 24 months or 2000 operating hours (whichever occurs first) of coverage.



PROTECTION PLUS EXTENDED WARRANTY

Enjoy total peace of mind with a Protection Plus® extended warranty. Providing the same level of protection as the standard warranty, Protection Plus also reflects different customer needs and expectations by offering a choice of durations and annual operating hours. According to your needs, you can benefit from the coverage for up to 5 years or 6000 engine hours. And Protection Plus is transferrable – so it will likely increase your machine's resale value.



Casted counterweight protects the tailgate

THERE'S NO TIME FOR DOWNTIME. STAND UP TO THE HARSHEST CONDITIONS. DAY AFTER DAY.



Changing filters



BOBCARE

A long-running machine starts with proper planned maintenance. Which protects against repair costs and unplanned failures when you're counting on your machine to work.

Avoid risk by preventing major repairs and complete failures.
Accomplish more by reducing downtime and increasing your productivity and profitability.

CHOOSE YOUR ANIMAL

E17

LINEUP

 CONVENTIONAL TAIL SWING
 Entry level "1.5 ton" excavator – designed for easy transportability.
 Transport weight below 1.6 tons





E17z

ZERO HOUSE SWING For operators looking for compactness and easy transportability.
 Transport weight close to 1.6 tons

E19

CONVENTIONAL TAIL SWING For experienced operators focusing on performance and operator comfort.

- Additional counterweight for excellent stability
- Joystick-controlled boom swing and auxiliary for greater comfort and accuracy with selectable auxiliary modes
- Autoshift travel motors to guarantee
 better traction and manoeuvrability





E20z

ZERO HOUSE SWING

For operators looking for compactness without sacrificing operator comfort and performance.

- Zero House Swing functionality (even with cab)
- Stability of best-in-class conventional machine
- Joystick-controlled boom swing and auxiliary for greater comfort and accuracy with selectable auxiliary modes
- Autoshift travel motors to guarantee better traction and manoeuvrability

STANDARD EQUIPMENT & OPTIONS

STANDARD EQUIPMENT & OPTIONS				
	E17	E17z	E19	E20z
PERFORMANCE				
2nd auxiliary hydraulics	-	-	•	•
980 mm dozer blade with two 190 mm blade extensions	1	~	1	√
Additional counterweight for excellent stability	-	-	•	-
Auxiliary hydraulic line on dipperstick	•	•	•	•
Auxiliary quick couplers	•	•	√	√
Double acting auxiliary hydraulics	√	√	√	√
Hydraulic clamp	-	-	•	•
Hydraulic joystick controls	√	√	√	√
Long dipperstick with clamp eyes	-	-	•	•
Long dozer blade	•	•	•	•
Object handling device (safety valves + overload warning device + lifteye)	•	•	•	•
Proportional and adjustable (3 modes) fingertip auxiliary hydraulic control	-	-	•	•
Proportional fingertip boom swing offset hydraulic control	-	-	•	•
Special applications kit	•	•	•	•
CAB & CANOPY				
AM/FM MP3 stereo radio	•	-	•	•
Beacon	•	•	•	•
Cupholders		√	√	√
Deluxe textile suspension seat (cab)	•	-	•	•
Fire extinguisher	•	•	•	•
Foldable & ergonomic pedals	√	√	√	√
Horn	√	√	√	√
Keyless ignition	•	•	•	•
Mirrors	•	•	•	•
Retractable seat belt	√	√	√	√
Storage compartment	√	-	√	-
TOPS/ROPS cab with heater	•	-	•	•
TOPS/ROPS/FOPS* canopy	\checkmark	√	√	√


STANDARD EQUIPMENT & OPTIONS				
	E17	E17z	E19	E20z
LIGHTS & BEACON				
Additional front lights and a rear light	•	•	•	•
LED lights set	-	-	•	•
Work light	√	√	√	√
MISCELLANEOUS				
Battery disconnect switch	√	√	√	√
Boom load holding valve	•	•	•	•
Boom, arm, bucket cylinder covers	•	•	•	•
Control console locks	√	√	\checkmark	√
Engine monitor with auto shutdown	√	√	√	√
Full fuel warning alarm	√	√	√	√
Grease gun set	•	-	•	-
HD travel hoses guard	•	•	•	•
Hydraulic and travel control lockouts	\checkmark	√	√	√
Hydraulically retractable undercarriage from 1360 to 980 mm	1	V	\checkmark	√
Upperstructure 4 point tie down	√	√	√	√
Warranty: 24 months or 2000 hours (whichever occurs first)	V	V	√	V
Water separator	√	√	√	√
TRACKS & TRAVEL				
230 mm rubber track	√	√	√	√
Auto shift drive motors	-	-	•	•
Travel motion alarm	•	•	•	•
2-speed travel	•	√	√	√

PERSONALIZE YOUR MACHINE

Sometimes, we all want to add a specific functionality or a personal touch to the machine. Choose from a list of comprehensive options and customize your mini excavator to your heart's content!



TOPS/ROPS cab with heater



 \checkmark = standard • = option - = not available

* Tip Over Protective Structure (TOPS) – Meets requirements of ISO 12117. Roll Over Protective Structure (ROPS) – Meets requirements of ISO 3471. Falling Object Protective Structure (FOPS) - Meets requirements of ISO 3449.



Fire extinguisher

LED lights



AM/FM stereo radio

DOZER BLADE OPTIONS

• Standard length for customers that prefer compactness for working in reduced spaces.

• Extended length for customers that prefer dustpanability and increased front stability.

All blades provide excellent departure angles and higher profile for better dozing performance.

MULTI-TOOL CARRIER

FIT FOR EVERYTHING

The wide range of attachments lets you adapt to any job in any environment. The hydraulic clamp and convenient design let you connect in seconds and prepare for any project that lies ahead.

- AugersBreakers
- Digging bucketsFlail mowerGrading buckets

- Hydraulic clamps
- Klac coupler

- Laser equipment
 Mechanical German type coupler (MS01)
 Mechanical German type coupler (MS01) with tilt function
 Mechanical pin grabber coupler
 Skeleton buckets

- Tilt buckets



Augers



Hydraulic clamps



Grading buckets



Tilt buckets

16

ĿВ

C I

Bobca

HB580

SPECIFICATIONS

SPECIFICATIONS				
	E17	E17z	E19	E20z
WEIGHTS				
Operating weight with canopy and bucket (ISO 6016)	1 711 kg	1 749 kg	_	_
Operating weight with cab and bucket (ISO 6016)	-	-	1 885 kg	2 019 kg
Transport mass (no attachment)	1 594 kg	1 632 kg	1 768 kg	1 902 kg
Weight reduction with canopy	-	-	-96 kg	-81 kg
Additional weight for cab with heating	96 kg		_	
Additional weight for counterweight		_	41 kg	-
Additional weight for long dipperstick	-	-	6 kg	6 kg
Additional weight for long dozer blade	9	kg	-	9 kg
Ground pressure with rubber tracks	29.4 kPa	30.06 kPa	32.4 kPa	31.1 kPa
ENGINE				
Make / model		Yanmar / 3TN	V74F-SPBC (Stage V)	
Fuel			Diesel	
Number of cylinders			3	
Displacement	993 cm ³			
Maximum power @ 2400 RPM (ISO 14396)	11 kW			
Maximum torque @ 1800 RPM (SAE J1995)	50.2 Nm			
HYDRAULIC SYSTEM				
Pump type	Triple gear pump		Dual piston pump with gear	r pump
Total hydraulic capacity	-	41.3 l/min	-	41.3 l/min
Piston pump capacity	-		30.0 l/min	
Gear pump capacity	32.5 l/min	-	41.3 l/min	-
Auxiliary flow (AUX1)	32.5 l/min		30 I/min	
Auxiliary relief (AUX1)	227 bar		180 bar	
Auxiliary flow (AUX2)	_	-		15 l/min
Auxiliary relief (AUX2)	_	-		179 bar
PERFORMANCE				
Digging force, dipperstick (ISO 6015)	91	08 N		10 371 N
Digging force, long dipperstick (ISO 6015)	_	_		9 279 N
Digging force, bucket (ISO 6015)	16 1	77 N		20 835 N
Drawbar pull	14 334 N	19 302 N	19 380 N	19 302 N
Travel speed, low range	2.1 km/h		.7 km/h	2.1 km/h
Travel speed, high range		4.3 km/h	·	4.2 km/h
SLEW SYSTEM				
Boom swing, left			80°	
Boom swing, right			60°	
Slew rate	8.7 RPM	10.1 RPM		8.4 RPM
FLUID CAPACITIES				
Fuel reservoir			191	

79 dB(A)

0.33 ms⁻²

0.51 ms⁻²

13.91

93 dB(A)

79 dB(A)

0.91 ms⁻²

1.78 ms⁻²

82 dB(A)

0.49 ms⁻²

1.32 ms⁻²

81 dB(A)

0.91 ms⁻²


1.78 ms⁻²

Certain specifications are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to

change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other

-	C
-	
	A
1	
G	


WORKING AREA




DIMENSIONS











E17z, E20z

E17, E19

Hydraulic reservoir

ENVIRONMENTAL

Noise level LpA (EU Directive 2006/42/EC)

Noise level LWA (EU Directive 2000/14/EC)

factors. Pictures of Bobcat units may show other than standard equipment.

Whole body vibration (ISO 2631-1)

Hand-arm vibration (ISO 5349-1)

DIMENSIONS & WORKING AREA

VORKING AREA						
	E17	E17z	E19	E20z		
A	196°					
В	3 919	3 971	4 084	4 134		
B *	-	-	4 257	4 307		
C	3 871	3 923	4 039	4 089		
C*	-	-	4 214	4 264		
D	1 526	1 560	1 542	1 592		
D*	-	-	1 561	1 611		
E		22	20			
E *	300	300	300	300		
F		20)4			
F*	254	254	254	254		
G	2 405	2 406	2 564			
H	3 371	3 378	3 573			
H*	-		3 701			
I.	2 370	2 369	2 566			
I*	-	-	2 693			
J	1 810		1 948			
J*	-		2 115			
K	2 249 2 385			85		
K *	-	-	2565			

DIMENSIONS						
	E17	E17z	E19	E20z		
A		23	35			
В		419				
C	1 340	1 138	1 340	1 138		
D		1 114		1 258		
E		1 0	45			
F	2 666	2 715	2 832	2 882		
G		1 476		1 620		
H	3 665	3 450	3 831	3 688		
H*	-	-	3 812	3 669		
Ι.,	25					
J	980					
J *	1 360					
K	2 299	2 297	2 299	2 297		
L -	230					
М	433	450	433	476		
N	589	638	589	638		
0	1 128	1 190	1 154	1 190		
Ρ	1 009	690	1 009	690		
Q	1 801	1 532	1 801	1 532		
R	1 645	1 370	1 645	1 370		

Values marked with * – Long dipperstick Unit: mm

FINANCING OPTIONS

24, 36, OR 48 MONTH FINANCING*

Take advantage of 24, 36 or 48 month financing programs starting from **0% interest** and improve your cash flow. Ask your dealer for the financing offers available.

100 MACHINES / 150 ATTACHMENT FAMILIES / 1 TOUGH ANIMAL



SKID STEER LOADERS



COMPACT TRACK LOADERS



COMPACT WHEEL LOADERS



SMALL ARTICULATED LOADERS



TELEHANDLERS



ROTARY TELEHANDLERS



LIGHT COMPACTION EQUIPMENT



MINI TRACK Loader



COMPACT EXCAVATORS



ATTACHMENTS



DOOSAN www.bobcat.com Bobcat is a Doosan Company. Doosan is a global leader in construction equipment, power & water solutions, engines, and engineering proudly serving customers and communities for more than a century. I Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries. ©2022 Bobcat Company. All Rights Reserved.

*Financing options may vary by country and dealer. Always ask your dealer about currently available financing options. Terms and conditions may apply.

Doosan Bobcat EMEA, U Kodetky 1810, 263 12 Dobříš, Czech Republic

©2022 BOBCAT B4500151-EN (08-22)